

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Reference number: EIGA097A

Issue date: 3/24/2017 Revision date: 6/20/2022 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Substance

Substance name : Oxygen (compressed)

CAS-No. : 7782-44-7
Product code : CA-1001-01251

Formula : O2

Commercial Name Oxygen (compressed), Lasal 2003, Aligal 3

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Test/Calibration gas, Industrial applications

1.3. Supplier

Air Liquide Canada Inc.

1250, René Lévesque West Blvd. Suite 1700

Montreal, QC, H3B 5E6

Canada

T 1-800-817-7697 www.airliquide.ca

1.4. Emergency telephone number

Emergency number : 514-878-1667

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Oxidizing gases Category 1 H270 May cause or intensify fire; oxidizer

Gases under pressure Compressed gas H280 Contains gas under pressure; may explode if heated

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA)





Signal word (GHS-CA) : Danger

Hazard statements (GHS CA) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS CA) : P370+P376 - In case of fire: Stop leak if safe to do so

P403 - Store in a well-ventilated place.

P410+P403 - Protect from sunlight. Store in a well-ventilated place. P220 - Keep away from clothing and other combustible materials.

P244 - Keep valves and fittings free from oil and grease.

2.3. Other hazards

Other hazards which do not result in classification : None.

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Chemical name/Synonyms	Product identifier	% V/V	Classification (GHS CA)
Oxygen (compressed)	-Dioxygen	CAS-No.: 7782-44-7	·	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Adverse effects not expected from this product. Remove victim to uncontaminated area wearing

self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. Remove victim to uncontaminated area.

First-aid measures after skin contact : Adverse effects not expected from this product. First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Adverse effects not expected from this product. Symptoms/effects after skin contact : Adverse effects not expected from this product. Symptoms/effects after eye contact : Adverse effects not expected from this product.

Symptoms/effects after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/effects upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

Most important symptoms and effects, both acute : Refer to section 11.

and delayed

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.3. Specific hazards arising from the hazardous product

Fire hazard : The product is not flammable.

Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire

and increasing risk of burns and injuries.

Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

6/20/2022 (Revision date) EN (English US) 2/12

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or

fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Exposure

to fire may cause containers to rupture/explode.

Protection during firefighting Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire

fighters. Do not enter fire area without proper protective equipment, including respiratory

protection.

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

> radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters Standard protective clothing and equipment (e.g, Self Contained Breathing Apparatus) for fire

fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective

gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Try to stop release. Evacuate area. Monitor concentration of released product. Wear

> self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Eliminate ignition sources. Ensure adequate air ventilation. Ensure adequate ventilation. Act in

accordance with local emergency plan. Stay upwind.

Personal Precautions, Protective Equipment and

Emergency Procedures

: EVACUATE ALL PERSONNEL FROM AFFECTED AREA. Use appropriate protective equipment. If leak is on user's equipment, be certain to purge piping before attempting repairs. If

leak is on a container or container valve contact the closest Air Liquide Canada location.

6.2. Methods and materials for containment and cleaning up

For containment : Try to stop release if without risk.

Methods for cleaning up : Dispose of contents/container in accordance with local/regional/national/international regulations.

Methods and material for containment and cleaning : Ventilate area.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or

in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use only with equipment rated for

cylinder pressure. Close valve after each use and when empty.

Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure.

> Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Keep equipment free from oil and grease. Use no oil or grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Use only oxygen approved lubricants and oxygen approved sealings. Use only with equipment cleaned for oxygen service and rated for container pressure. Avoid suck back of

water, acid and alkalis. Do not breathe gas.

6/20/2022 (Revision date) EN (English US) 3/12

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Safe handling of the gas receptacle

Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

Incompatible products Incompatible materials

Conditions for safe storage, including any incompatibilities

: Comply with applicable regulations.

: Do not expose to temperatures exceeding 52 °C/ 125 °F. Keep container closed when not in use. Protect containers from physical damage; do not drag, roll, slide or drop. Store in well ventilated

: None known.

: Flammable materials. Combustible materials. Reducing agents.

Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Segregate from flammable gases and other flammable materials in store. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information : None available.

8.2. Appropriate engineering controls

Appropriate engineering controls

Environmental exposure controls

: Provide adequate ventilation. Ensure exposure is below occupational exposure limits (where available). Provide adequate general and local exhaust ventilation. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages.

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

opcomo metrodo for waste gas trea

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Safety shoes. A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

Hand protection:

Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Eye protection:

Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications

Skin and body protection:

Wear suitable protective clothing, e.g. lab coats, coveralls or flame resistant clothing.

Respiratory protection:

None necessary during normal and routine operations. See Sections 5 & 6.

Personal protective equipment symbol(s):









Thermal hazard protection:

None necessary during normal and routine operations.

Other information:

Vapor pressure at 50 °C

Standard EN ISO 14116 - Limited flame spread materials. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colorless gas.
Color : Colorless.
Odor : Odorless

Odor threshold : Odor threshold is subjective and inadequate to warn for overexposure

No data available

pH : Not applicable for gases and gas mixtures.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

Molecular mass : 17 g/mol Melting point : -219 °C

Freezing point : No data available

Initial Boiling point and boiling range $: -181.95 \, ^{\circ}\text{C-}$ No data available for the boiling range

Flash point : Not applicable - not flammable

Critical temperature : -117.55 °C

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Flammability (solid, gas) : See Section 2.1 and 2.2

Non flammable.
: 28.1 mbar 23°C
: Not applicable.
: 5043 kPa

Critical pressure : 5043
Relative vapor density at 20 °C : 1.105
Relative density : 1.1

Density : 1.4289 kg/m³ (at 21.1 °C)

Relative gas density : 1.1

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Solubility : Water: 39 mg/l

Partition coefficient n-octanol/water (Log Pow) : Not applicable for inorganic products.

Not applicable for gas-mixtures.

Viscosity, kinematic : No reliable data available.
Viscosity, dynamic : No reliable data available.

Explosive properties : Not applicable.

Oxidizing properties : Not combustible but enhances combustion of other substances. May intensify fire. Oxidizer.

Oxidiser.

Explosion limits : Not applicable - not flammable

UEL Not applicable LEL Not applicable

Ci : 1

9.2. Other information

Additional information : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level

SECTION 10: Stability and reactivity

Reactivity : None known.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Violently oxidises organic material.

Conditions to avoid : None under recommended storage and handling conditions (see section 7). Avoid moisture in

installation systems.

Incompatible materials : Combustible materials. Flammable materials. Reducing agents. May react violently with

combustible materials. May react violently with reducing agents. Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu. For additional information on compatibility refer to

ISO 11114.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be

produced. None.

Hardening time: : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified.

Oxygen (compressed) (7782-44-7)	
LC50 Inhalation - Rat [ppm]	800000 ppm/4h
ATE CA (Gases (except aerosol dispensers and lighters))	800000 ppmV/4h

Skin corrosion/irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Serious eye damage/irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

Oxygen (compressed) (7782-44-7)

Viscosity, kinematic No reliable data available.

Symptoms/effects after inhalation : Adverse effects not expected from this product. Symptoms/effects after skin contact Adverse effects not expected from this product. Symptoms/effects after eye contact Adverse effects not expected from this product.

Symptoms/effects after ingestion Ingestion is not considered a potential route of exposure.

Symptoms/effects upon intravenous administration Not known. : Refer to section 11.

Most important symptoms and effects, both acute

and delayed

Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

: No ecological damage caused by this product. Ecology - general

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

: Not classified

12.2. Persistence and degradability

Oxygen (compressed) (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

Oxygen (compressed) (7782-44-7)	
Bioaccumulative potential	No ecological damage caused by this product.
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas-mixtures.

12.4. Mobility in soil

Oxygen (compressed) (7782-44-7)	
Ecology - soil	No ecological damage caused by this product.
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.
Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas-mixtures.

12.5. Other adverse effects

: Not classified Ozone Effect on ozone layer

Other adverse effects : No known effects from this product.

Effect on global warming : None.

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Contact supplier if guidance is required. May be vented to atmosphere in a well ventilated place.

Ensure that the emission levels from local regulations or operating permits are not exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org for more guidance on suitable disposal methods. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original container to

upplier.

Product/Packaging disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for

more guidance on suitable disposal methods.

Additional information : External treatment and disposal of waste should comply with applicable local and/or national

regulations.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

 UN-No. (TDG)
 : UN1072

 DOT NA No
 : UN1072

 UN-No. (IMDG)
 : Not applicable

 UN-No. (IATA)
 : Not applicable

14.2. UN proper shipping name

Proper Shipping Name : OXYGEN, COMPRESSED
Proper Shipping Name (DOT) : Oxygen, compressed
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 2.2 (5.1) Hazard labels (TDG) : 2.2, 5.1





DOT

Transport hazard class(es) (DOT) : 2.2 (5.1) Hazard labels (DOT) : 2.2, 5.1





IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

:

14.4. Packing group

Packing group (TDG): Not applicablePacking group (DOT): Not applicablePacking group (IMDG): Not applicablePacking group (IATA): Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure cylinder valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is correctly fitted.

TDG

UN-No. (TDG) : UN1072

TDG Special Provisions : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly

contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required

to be shown on a small means of containment:
(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or

(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.

: 3 000

Explosive Limit and Limited Quantity Index : 0.125 L Excepted quantities (TDG) : E0

Passenger Carrying Ship Index : Forbidden
Passenger Carrying Road Vehicle or Passenger : 75 L

Passenger Carrying Road vehicle of Passenger

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 122 (UN1072)

DOT

ERAP Index

UN-No.(DOT) : UN1072

DOT Special Provisions (49 CFR 172.102) : 110 - Fire extinguishers transported under UN1044 may include installed actuating cartridges

(cartridges, power device of Division 1.4C or 1.4S), without changing the classification of Division 2.2, provided the aggregate quantity of deflagrating (propellant) explosives does not exceed 3.2

grams per extinguishing unit.

A14 - This material is not authorized to be transported as a limited quantity or consumer commodity in accordance with 173.306 of this subchapter when transported aboard an aircraft.

6/20/2022 (Revision date) EN (English US) 9/12

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Quantity Limitations Passenger aircraft/rail (49 : 75 kg

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location

: 150 kg

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel, D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

Oxygen (compressed) (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

Oxygen (compressed) (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Oxygen (compressed) (7782-44-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Oxygen (compressed) (7782-44-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Issue date : 03/24/2017 Revision date : 06/20/2022

Training advice : Ensure operators understand the hazard of oxygen enrichment.

Full text of H-phrases:	
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated

Abbreviati	ons and acronyms:
	ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Abbreviations and acronyms:	
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

Safety Data Sheet (SDS), Canada

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.